

Fully Biodegradable, Very Low Odour High performance Formwork Release Agent

NATUROL CR3 is a blend of natural vegetable oils in a new, very low odour solution to create a high performance chemical release agent for all site and precast use, especially for indoor use. It achieves a very high quality concrete finish and is suitable for all modern mould surfaces. Naturol CR3 will aid elimination of blowholes and provide a clean uniform and non-stained surface.

Advantages

- Essentially non-hazardous and biodegradable.
- Suitable for use on all types of formwork and pre-cast mould materials, including polystyrene, GRP, plastic and metal
- It is a suspension and sediment free, highly mobile liquid, which can be used in very fine sprays without clogging the jets.
- Odour Free, even when using a fine fog spray.
- Very economic coverage rates can be obtained without difficulty.
- Retains its mobility at low temperatures.
- It may be applied immediately prior to casting, or treated forms may be left until apparently dry.
- The chemical reaction promotes a uniform, matt, stain free, concrete surface with reduced incidence of blow holes and surface blemishes.
- Continued use gives progressively better results on timber formwork.
- Can be used with grey or white cement.
- Provides a quick, positive release of formwork, reducing labour costs and damage to formwork and moulds.

Application

NATUROL CR3 is supplied ready for use and should not be diluted. It should be applied as thinly and evenly as possible for optimum performance. It can be applied to all types of formwork by spray, fine-haired brush, swab or roller. Any excess should be mopped up. For the best and most economical performance, application by fine fog spray is recommended. It will not clog fine jets even at freezing temperatures. For new 'unsealed' timber forms pre-treatment is recommended with a second coat applied prior to use.

Coverage

A thin coating spray applied to give a coverage area of between 30 to 40m² per litre (depending upon surface porosity) is recommended. Excessive application of NATUROL CR3 may be detrimental to the concrete surface finish; care should therefore be taken to ensure that NATUROL CR3 is applied as recommended to achieve optimum performance and maximum economy.

Storage

NATUROL CR3 in manufacturer's sealed drums requires no special storage facilities. This type of material should be applied in well ventilated areas.

Shelf Life

Practically unlimited in sealed containers.

Specification

NATUROL CR3 mould release agent is manufactured by Adomast Manufacturing Ltd and shall be applied strictly in accordance with the manufacturer's instructions. For specific advice regarding any aspect of this product, please consult our Technical Department.

Health and Safety

Prolonged physical contact should be avoided and personal and environmental hygiene encouraged in common with the use of all mould release agents. Where contact with skin occurs, the material should be removed with soap and water. If splashes affect eyes, they should be bathed immediately with copious quantities of clean water and if discomfort persists, medical attention should be sought without delay.

See Safety Data Sheet for further information.