

Wraptite® Liquid Flashing Black

AIR BARRIERS

PRODUCT: Wraptite Liquid Flashing Black
COMPOSITION: Sealants for facade for exterior and interior application
STANDARDS: EN 15651-1:2012 AVCP 3
APPROVED BODY: 1119

Physical Properties	Test Method	Mean results
Reaction to fire	EN 15651-1:2012	Class E
Release of chemicals dangerous to the environment and health		NPD
Resistance to flow		≤ 3 mm
Loss of volume		≤ 10 %
Tensile properties (i.e. elongation) at maintained extension after water immersion (elastic)		NF at 100 % Elongation
Tensile properties (i.e. at secant tensile modulus) for non-structural low modulus sealants used in joints in cold climate areas (-30°)		≤ 0.9 MPa at 100 % Elongation
Tensile properties (i.e. at maintained elongation) for nonstructural sealants used in joints in cold climate areas (-30°)		NF at 100 % Elongation
Durability		Pass

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Manufactured By:

The A. Proctor Group Ltd.
 The Haugh
 Blairgowrie
 United Kingdom
 PH10 7ER

Telephone: +44(0)1250 872261
Fax: +44(0)1250 872727
Web: www.proctorgroup.com

Signed for and on behalf of The A. Proctor Group Ltd.

Name:

Position: Technical Director

Place: The Haugh, Blairgowrie Date: 17.05.22



Download a brochure from
 our website...

www.proctorgroup.com

contact@proctorgroup.com | +44 (0) 1250 872261

Issued March 2022

