Denso Anti-Slip Tape

Reduces risk of slip at home and at workplaces

Composition

Denso Anti-Slip Tape consists of a self-adhesive PVC tape coated on one surface with a layer of acrylic adhesive. The upper surface is coated with a layer of aluminium oxide particles. The adhesive surface is protected by a plastic film interleaving which is discarded during application. The tape is supplied in roll form.

Uses

Denso Anti-Slip Tape is a self-adhesive tape designed for both indoor and outdoor use on smooth surfaces. The tape can be applied by hand to steps, paths, patios, garage floors and decking.

Service Temperature: maximum +80°C

Characteristics

Denso Anti-Slip Tape:

- prevents slips,
- is easy to apply, and
- has excellent adhesion to most surfaces.

Application

See *Instructions for Use* for additional details.

Ensure the surface is clean, dry and free from any contamination or greasy residues. All porous surfaces should be sealed prior to application using a good quality primer, allow to dry.

Application Temperature: +10°C to +45°C

Application limitations

Suitable for smooth surfaces only. Not suitable for grooved decking, the tape must be in full contact with the surface it is to be applied to, across the complete width of the tape with no gaps or voids.

Availability

Denso Anti-Slip Tape is available in Black, Yellow, Clear and Hazard, in 3 m or 18 m roll length and 50 mm roll width.

Storage conditions

Store in a dry place in original packaging. Shelf life between 12 – 24 months.

Waste material

Please avoid or minimise waste wherever possible. Please do not discard waste material, including packaging, in the surrounding environment. Follow all relevant legislation for disposal.

Typical Properties

Total thickness	1.02 mm	
Weight	0.6 kg/m^2	
Tensile Strength	6.0 kg/25.4mm^2	PSTC-31
Elongation at Break	25%	PSTC-31
Adhesion to Steel	1.5 kg/25.4 mm^2	PSTC-4

Note: Denso Anti-Slip Tape is not suitable for industrial applications or continuous immersion and cannot be overpainted. To ensure continued effectiveness, periodic inspections should be carried out and strips of new tape re-applied in the event of wear/damage or the tape having disbonded or been affected by weather conditions. Please note that Winn & Coales (Denso) Ltd accepts no responsibility whatsoever for any accidents or injuries that could still occur where Denso Anti-Slip Tape has been applied.

Important: Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Winn & Coales (Denso) Ltd operate a Quality Management System registered to ISO 9001 (BSI Certificate no. FM01548) and an Environmental Management System registered to ISO 14001 (BSI Certificate no. 583748).

WINN & COALES (DENSO) LTD
Denso House, 33-35 Chapel Road,
London, SE27 0TR
United Kingdom

TEL: +44 (0) 20 8670 7511
FAX: +44 (0) 20 8761 2456
WEB: www.denso.net
EMAIL: mail@denso.net