Denso Skid Resistant Overbanding Tape

A cold applied skid resistant bituminous tape for sealing of pavement cracks

Composition
Denso Skid Resistant Overbanding Tape is a thick, polymer modified bituminous adhesive layer with a rubber-based backing in tape form with a disposable release film.

Uses
Denso Skid Resistant Overbanding Tape is used for surface sealing of cracks or failed reinstatement joints up to 5 mm wide in road pavements on secondary roads. Once applied, the tape provides a skid resistant surface.

Characteristics
Denso Skid Resistant Overbanding Tape;

- has excellent resistance to water, acids, alkalis and salts,
- prevents further cracking and spalling of the road surface, and
- has a skid resistant surface.

Application
See *Instructions for use* for details. Denso Skid Resistant Overbanding Tape is suitable for both hand and machine application. For machine application Denso roller 75 applicator is recommended.

Recommended primer: Denso Primer D

Application Temperature: +8°C to +45°C

Availability
Denso Skid Resistant Overbanding Tape is available in 10 m lengths with a 30 mm or 40 mm width. Rolls per carton;
30 mm width – 10 rolls
40 mm width – 8 rolls

Storage Conditions
Store in a cool and dry place in original packaging.

Waste Material
Please apply the waste hierarchy to avoid or minimise waste wherever possible. Please do not discard waste material, including packaging, in the surrounding environment. Follow all relevant legislation for disposal.

Typical Properties

Colour	Black
Thickness	2.8 mm
Core Size	76 mm I.D.
Softening point	120°C
Skid Resistance (TRL Road Note 27)	Dry 67 Wet 66 Exceeds Dept for Transport Requirement

Important: Winn & Coales (Denso) Ltd pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. Winn & Coales (Denso) Ltd operate a Quality Management System registered to BS EN ISO 9001 (BSI Certificate no. FM01548) and an Environmental Management System registered to BS EN 14001 (BSI Certificate 583748).

WINN & COALES (DENSO) LTD
Denso House, 33-35 Chapel Road,
London, SE27 0TR
United Kingdom

TEL: +44 (0) 20 8670 7511
FAX: +44 (0) 20 8761 2456
WEB: www.denso.net
EMAIL: mail@denso.net